




Ref. 1462-C


GENERAL CHARACTERISTICS

- Maintenance-free, brush-less drive motor,
- Microprocessor control of spinning parameters provides high repeatability of results
- LCD display of actual parameters: speed, time and relative centrifugal force.
- Optimization of acceleration and deceleration force.
- Wide range of exchangeable rotors, and wide range of other accessories
- “Short” spinning function.
- Unbalance protection system.
- Inspection glass.
- It is not possible to open the lid, during spinning.
- It is not possible to start, when the lid is open.

Product according to national and international safety regulations EN-61010-1, EN-61010-2-020.

Ref	Dimensions W x H x D	Weight	Consumption W
1462-C	355x270x435mm.	10,5Kg	55
Capacity	Max. R.p.m	Max. RCF	
4 citoset 1,2ml.	300 / 2500	750 xg.	
Maintenance-free	Timer	Voltage	Brushless
Yes	1-99min ∞	130/250v. 50/60Hz.	Yes
Display	Rotor identification	Refrigerant	Temperature range
LCD	NO	NO	---

Rotor		Accessories information			
	8x10ml.	Accessories	Ø x Long	Tubes	Ref.
	Ø17x100/110mm				
	Swing out Max. 2500 R.p.m. Max. 750 xg	Round carriers 5ml.	Ø13x75mm.	8	4088
		Round carriers 7ml.	Ø13x100mm	8	4082
Ref. 1462-2193C					

Rotor		Accessories information			
	4x10ml.	Accessories	Ø x Long	Tubes	Ref.
	Ø17 x 85mm				
	Swing out Max. 2500 R.p.m. Max. 750 xg	Round carriers 5ml.	Ø13x75mm.	4	4088
		Round carriers 7ml.	Ø13x100mm	4	4082
Ref. 1462-2331C					