



Ref. 1203



Ref. 1200



Ref. 1203

GENERAL CHARACTERISTICS

A set of magnetic stirrers with or without heating that offers the user an excellent price/quality ratio. The common characteristics are the following:

- An injected housing that provides the equipment with great stability, painted in epoxy.
- 150mm \varnothing stirring surface made of AISI 304 stainless steel or ceramic.
- Modularly designed electric heating and/or stirring circuits for easy replacement.
- Illuminated switches and separate adjustment controls for the heating and stirring functions located on the front panel.
- The stirring capacity exceeds 10l (relative to water).
- Stirring speed variable between 30 and 2100 r.p.m.
- Includes Teflon-insulated magnet 8 \varnothing x 40 mm
- For the stirrers with heating, they use a shielded heating element system and include an indicator light to signal heating.

Manufactured according to CE standards.



Ref.	Heating	Power (W)	Max temp. (°C)	Dimensions (mm) W x H x D	Control system	Weight (Kg)
1200	no	10	-	180 x 110 x 220	-	2
1201	yes	500	400 On surface	180 x 125 x 220	Electronic regulator that provides from 10 to 100% of the heating power, outlet for a contact thermostat	3
1203	yes	500	300 On surface	180 x 125 x 220	Adjustable temperature by means of bulb thermostat with a precision of $\pm 3^{\circ}\text{C}$.	3

Ref.	Accessories
1220	Safety ring
1221	Support bar of 12mm \varnothing x 450mm
1735	Digital programmer
1736	TCD-1 (Digital Contact Thermometer)
1234	Cylindrical magnet of 6mm diameter and 20mm length
1236	Cylindrical magnet of 6mm diameter and 30mm length
1237	Cylindrical magnet of 6/8mm diameter and 35mm length
1238	Cylindrical magnet of 8mm diameter and 40mm length
1239	Cylindrical magnet of 8mm diameter and 50mm length