

# 115L. DRYING OVEN WITH NATURAL AIR CONVECTION Ref. 8304

## **GENERAL CHARACTERISTICS**

- \* Interior and exterior construction in stainless steel AISI 304.
- \* Solid door, fitted with a key. Excellent thermal insulation.
- \* Protection against overtemperature class 2.0 according to DIN 12880.
  - \* 4,3", clear, full colour touch screen.
  - \* USB and LAN ports for data transfer
- \* Multi-segment time and temperature programs. Loop function up to 255 times or endless.

\* Adjustable start delay feature, adjustable ramps.

\* Recording of min, average and max temperature value for each segment overview of set and

#### current parameters while operating.

- \* Operating in temperature or time priority mode.
- \* Fan speed control in the range of 0 ... 100% or 10% ... 100% (depending on the chamber

capacity).

\* Temperature sensor fail alarm.

- \* Possibility of temperature calibration by the User.
- \* Power failure control system (program continued after restoring power).

\* Visual and sound alarm.





### \* Quick change of program parameters.

#### \* Alarm Bar.

#### \* Shelves standard included 2, possibility of including 7. Max shelf workload 25Kg.

Manufactured according to CE directives.

Ref.	Capacity	Dimensions W x H x D	Useful measures (W x H x D)	Weight	Temperature	Nominal power
8304	115L.	650 x 850 x 710mm.	460 x 540 x 450mm.	65 Kg.	Up to 300°C	2500

Ref	Accesories		
8300-02		Stainless steel wire shelf INOX	
8300-03		Perforated shelf	
8300-04		Reinforced shelf	
8300-05		Reinforced version	
8300-06	1, 2, 3,	Door openings counter	
8300-07	A	Table with wheels	
8300-08		Additional Pt 100 temperature sensor	
8300-09		HEPA-fresh air filter	
8300-10		Wheels	
8300-11		Non-standard access port for external sensor	





BUNSEN SA. 30 Rio Alberche St - 28970 Humanes de Madrid, Madrid, SPAIN Tlf. +34 916 113 584 - Fax. +34 916 128 254 <u>info@bunsen.es</u> - <u>www.bunsen.es</u>

