



www.bunsen.es



MAGNETIC STIRRER

Ref. 1201

GENERAL CHARACTERISTICS

- * An injected housing that provides the equipment with great stability, painted in epoxy.
 - * 150 mm Ø stirring surface made of AISI 304 stainless steel.
- * Modularly designed electric heating and/or stirring circuits for easy replacement.
- * Illuminated switches and separate adjustment controls for the heating and stirring functions located on the front panel.
 - * The stirring capacity exceeds 10 l (relative to water).
 - * Stirring speed variable between 30 ÷ 2100 r.p.m.
 - * Include an indicator light to signal heating.
- * Electronic heating regulation; 0 ÷ 100% heat power.
 - * Includes Teflon-insulated magnet 8 Ø x 40 mm.

Manufactured according to CE standards.



BUNSEN SA. C/ Río Alberche, 30, - 28970 - Humanes de Madrid, Madrid. SPAIN
Tlf. +34 916 113 584 - Fax. +34 916 128 254
info@bunsen.es - www.bunsen.es



Ref	Max temp. on Surface (°C)	Power (W)	Dimensions (W x H x D, mm)	Weight (Kg)	Control system
1201	400	500	180 x 125 x 220	3	Electronic regulator that provides from 10 to 100% of the heating power, with an outlet for a contact thermostat

Ref	Accessories
1220	Safety ring
1221	Support bar of 12 mm Ø x 450 mm
1736	TCD-1 (Digital Contact Thermometer)
1234	Cylindrical magnet of 6 mm diameter and 20 mm length
1236	Cylindrical magnet of 6 mm diameter and 30 mm length
1237	Cylindrical magnet of 6/8 mm diameter and 35 mm length
1238	Cylindrical magnet of 8 mm diameter and 40 mm length
1239	Cylindrical magnet of 8 mm diameter and 50 mm length



BUNSEN SA. C/ Río Alberche, 30, - 28970 - Humanes de Madrid, Madrid. SPAIN
Tlf. +34 916 113 584 - Fax. +34 916 128 254
info@bunsen.es - www.bunsen.es

