





## THERMOSTATIC BATH 5L. 200°C.

Ref. 1603

## **GENERAL CHARACTERISTICS**

- \* Double wall construction: the exterior made of aluminum painted in epoxy and the interior basin made of 18/10 stainless steel.
  - \* Heating by a heating element shielded by AISI 316 stainless steel.
  - \* Temperature regulation from room temperature up to 200°C by bulb thermostat.
  - \* Equipped with a safety thermostat that has a manual reset in accordance with DIN12877, class 2.
    - \* Control panel includes:
      - \* Iluminated ON switch.
      - \* Indicator light showing heating element operation.
      - \* Safety thermostat indicator light.
      - \* Temperature adjustment selector.

Manufactured according to CE directives.





Ref	Capacity	Weight	Power	Useful measures (W x H x D)	Ext. measures (W x H x D)	Máx Temp.	Stability °C
1603	5L.	4Kg.	1000W.	290 x 150 x 140mm.	370 x 200 x 280mm.	200°C	±2

Ref	Accessories
1630	Stainless steel cover with 2 openings and reduction disks.
1640	Top cover
1650	Element cover
1660	Blank cover
1663	Drain tap
1680	Hinge for top cover ref. 1640
CHB 060	Racks for baby bottles (3 baby bottles)
1600-10-1	Racks (265x120 mm) for 98 test tubes, Ø 10-12 mm
1600-10-2	Racks (265x120 mm) for 72 test tubes, Ø 14-16 mm
1600-10-3	Racks (265x120 mm) for 50 test tubes, Ø 18-20 mm
1600-3	Liquid level indicator (factory installed)
	Different platform sizes upon client's request









