



www.bunsen.es



DIGITAL BATH 5L.

Ref. 1611

GENERAL CHARACTERISTICS

- * Double wall, metal construction: exterior painted in epoxy with antioxidant treatment and interior basin made of 18/10 stainless steel.
- * Heating by shielded heating element made of AISI 316 stainless steel.
- * Digital temperature control by digital thermostat controlled by microcontroller from environment + 5° to 99.9°C. Resolution, 0.1°C.
- * Equipped with a safety thermostat adjustable that has a manual reset in the event of over-temperature according to DIN 12877, class 2.
- * Control panel includes:
 - * Illuminated ON switch.
 - * Indicator light showing heating element operation.
 - * Safety thermostat indicator light.
 - * Display control.

Manufactured according to CE directives.



BUNSEN SA. C/ Río Alberche, 30, - 28970 - Humanes de Madrid, Madrid. SPAIN
Tlf. +34 916 113 584 - Fax. +34 916 128 254
info@bunsen.es - www.bunsen.es



Ref	Capacity	Probe	Power	Useful measures W x H x D	Ext. measures W x H x D	Max. temp	Precision °C
1611	5L.	NTC	700W.	290 x 150 x 140mm.	370 x 200 x 280mm.	99.9°C	±0.5%

Ref	Accessories
1630	Stainless steel cover with 2 openings and reduction disks
1640	Top cover
1650	Element cover
1660	Blank cover
1663	Drain tap
1680	Hinge for top cover ref. 1640
CHB 060	Racks for baby bottles (3 baby bottles)
1600-10-1	Racks (265x120 mm) for 98 test tubes, Ø 10-12 mm
1600-10-2	Racks (265x120 mm) for 72 test tubes, Ø 14-16 mm
1600-10-3	Racks (265x120 mm) for 50 test tubes, Ø 18-20 mm
1600-3	Liquid level indicator (factory installed)
	Different platform sizes upon client's request



BUNSEN SA. C/ Río Alberche, 30, - 28970 - Humanes de Madrid, Madrid. SPAIN
Tlf. +34 916 113 584 - Fax. +34 916 128 254
info@bunsen.es - www.bunsen.es

