

15L. DRYING OVEN WITH FORCED AIR CONVECTION Ref. 8307

GENERAL CHARACTERISTICS

* Interior and exterior construction in stainless steel AISI 304.

- * Solid door, fitted with a key. Excellent thermal insulation.
- * Protection against overtemperature class 2.0 according to DIN 12880.

* 4,3", clear, full colour touch screen.

- * USB and LAN ports for data transfer
- * Multi-segment time and temperature programs. Loop function up to 255 times or endless.

* Adjustable start delay feature, adjustable ramps.

* Recording of min, average and max temperature value for each segment overview of set and

current parameters while operating.

* Operating in temperature or time priority mode.

* Fan speed control in the range of 0 ... 100% or 10% ... 100% (depending on the chamber

capacity).

* Temperature sensor fail alarm.

* Possibility of temperature calibration by the User.

* Power failure control system (program continued after restoring power).

* Visual and sound alarm.

* Quick change of program parameters.





* Alarm Bar.

- * Automatic fan shut-down after completing the program. Automatic fan air-flap control.
 - * Shelves standard included 1, possibility of including 2. Max shelf workload 10Kg.

Manufactured according to CE directives.

Ref.	Capacity	Dimensions W x H x D	Useful measures (W x H x D)	Weight	Temperature	Nominal power
8307	15L.	510 x 550 x 470mm.	320 x 230 x 200mm.	27 Kg.	Up to 300°C	700

Ref	Accesories		
8300-02		Stainless steel wire shelf INOX	
8300-03		Perforated shelf	
8300-04		Reinforced shelf	
8300-05		Reinforced version	
8300-06	1, 2, 3,	Door openings counter	
8300-07	JA .	Table with wheels	
8300-08		Additional Pt 100 temperature sensor	
8300-09		HEPA-fresh air filter	
8300-10		Wheels	
8300-11		Non-standard access port for external sensor	





BUNSEN SA. 30 Rio Alberche St - 28970 Humanes de Madrid, Madrid, SPAIN Tlf. +34 916 113 584 - Fax. +34 916 128 254 <u>info@bunsen.es</u> - <u>www.bunsen.es</u>

