

DRYING OVEN



400L. DRYING OVEN WITH FORCED AIR CONVECTION Ref. 8330 Plus

GENERAL CHARACTERISTICS

- * Interior and exterior construction in stainless steel AISI 304.
- * Solid door, fitted with a key. Excellent thermal insulation.
- * Protection against overtemperature class 3.1 according to DIN 12880.

* USB port. Resolution 0.1°C.

- * PID microprocessor controller with a large (5,7") full colour touch screen, intuitive menu and user friendly software. They can be connected to Ethernet network for remote control.
- * Administrator function to manage User accounts
- * Access control via login. 7 days programming.
- * multi-segment temperature-time profile (up to 100). Loop function up to 99 times or endless.
- * Adjustable start delay feature (from 1 min to 99:59 h).
- * Overview of set and current parameters while operating. Adjustable ramps.
- * Recording of min, average and max temperature value for each segment.
- * Possibility of temperature calibration by the user.
- * Auto-diagnostic function. Automatic air-flap control.
- * Automatic fan shut-down after completing the program.
- * Audible and visual temperature alarm.
- * Power failure control system (program continued after restoring power).



BUNSEN SA. C/Tokio, 2 28970 Humanes de Madrid, Madrid, SPAIN Tlf. +34 916 113 584 - Fax. +34 916 128 254 info@bunsen.es - www.bunsen.es



* Trays made of stainless steel wire; 3 tray included, maximum capacity; 14. Max shelf workload 25 kg. Consult accessories.

* Real time clock.

* Internal memory to store up to 4100 data records. And 20 user programs memory with password protected settings.

Manufactured according to CE directives.

Ref.	Capacity	Dimensions W x H x D	Useful measures W x H x D	Weight	Temperature	Nominal power
8330P	400L.	1100 x 1430 x 780mm.	800 x 1040 x 510mm.	174 Kg.	Up to 300°C	4000W

Ref	Accesories	
8300-02		Stainless steel wire shelf INOX
8300-03		Perforated shelf
8300-04		Reinforced shelf
8300-05		Reinforced version
8300-06		Interior led lighting
8300-07	A	Table with wheels
8300-08		Additional Pt 100 temperature sensor
8300-09		HEPA-fresh air filter
8300-10	5.5	Wheels
8300-11		Non-standard access port for external sensor



