




<u>www.bunsen.es</u>





75L. DRYING OVEN WITH FORCED AIR CONVECTION Ref. 8310

GENERAL CHARACTERISTICS

- * Interior and exterior construction in stainless steel AISI 304.
- * Solid door, fitted with a key. Excellent thermal insulation.
- * Protection against overtemperature class 2.0 according to DIN 12880.
 - * 4,3", clear, full colour touch screen.
 - * USB and LAN ports for data transfer
- * Multi-segment time and temperature programs. Loop function up to 255 times or endless.
 - * Adjustable start delay feature, adjustable ramps.
- * Recording of min, average and max temperature value for each segment overview of set and current parameters while operating.
 - * Operating in temperature or time priority mode.
- * Fan speed control in the range of 0 ... 100% or 10% ... 100% (depending on the chamber capacity).
 - * Temperature sensor fail alarm.
 - * Possibility of temperature calibration by the User.
 - * Power failure control system (program continued after restoring power).
 - * Visual and sound alarm.
 - * Quick change of program parameters.





* Alarm Bar.

- * Automatic fan shut-down after completing the program. Automatic fan air-flap control.
 - * Shelves standard included 2, possibility of including 5. Max shelf workload 25Kg.

Manufactured according to CE directives.

Ref.	Capacity	Dimensions W x H x D	Useful measures (W x H x D)	Weight	Temperature	Nominal power
8310	75L.	590 x 850 x 620mm.	400 x 530 x 360mm.	60 Kg.	Up to 300°C	1700

Ref	Accesories		
8300-02		Stainless steel wire shelf INOX	
8300-03		Perforated shelf	
8300-04		Reinforced shelf	
8300-05		Reinforced version	
8300-06	1, 2, 3,	Door openings counter	
8300-07	兩	Table with wheels	
8300-08		Additional Pt 100 temperature sensor	
8300-09		HEPA-fresh air filter	
8300-10	500	Wheels	
8300-11		Non-standard access port for external sensor	





